

KABA®

E-Plex E5800

NEW

E-Plex E5800

The Only Stand-Alone FIPS 201 Compliant Products that are GSA Approved and Listed on Approved Product List (APL)

- PIN/PIPS 201 Card or Dual Credential
- Electronic Pushbutton Lock/Card Access
- 3,000 Access Codes
- 30,000 Audit Events
- Access Schedules
- ANSI/BHMA Grade 1 Certified



Like all other Kaba E-Plex card-based products, the E5800 Series Locks and SACs offer the convenience of Kaba's new LearnLok™ feature allowing up to 300 FIPS 201 cards to be enrolled at the lock's reader without the use of software for basic access control.

Optional Software: For management of up to 3,000 users per door and more advanced security features, optional software maybe used.

Personal ID Verification Interface: Contactless Interface ISO14443A (and B when available)

ID Card Enrolling Station: Contact Interface Card Reader/Enroller (ISO7816-4)

Optional Contactless Interface Card Reader/Enroller

Lock Programming an Auditing Unit: Handheld PDA with IrDA communications

Authority Levels (6): Authority levels allow you to control who has access to specific lock operations:

- Master • Guest/Visitor User • Manager • Service User • Access User • Maintenance Unit (PDA) User

Passage Mode Options (3):

First manager or privileged-user in Automatic according to access schedules Manually toggled on/off at the lock keypad

Battery Operation:

Batteries located in interior housing cover; offers quick and easy battery replacement for institutions (Four AA Alkaline batteries provide up to 180,000 cycles). Lock data is maintained if batteries fail.

Ease of Installation: LectroBolt™ (patent pending) eliminates wiring to or through the door—no risk of pinched wires

Construction: Extra heavy-duty Grade1 lock; cylindrical lockset, solid cast housings; solid cast zinc levers, cylindrical drive wear tested for extensive use in indoor and outdoor applications

Numeric Keypad: Vandal resistant, solid metal push buttons

Non-handed: pre-assembled for left-hand door installation— easily changed in the field

Backset: Cylindrical: 2-3/4" (70mm)

Minimum Stile Required: 5" (127mm)

KeyOverride: Interchangeable Cores: Small format— Best and equivalent (6 or 7-pin length)

Accessibility Standard: Americans with Disabilities Act (ADA)

Fire Rating: 3-hour, UL/ULC fire door rating for "A" labeled doors

Durability: ANSI/BHMA Grade1 certified (A156.25, A156.2, A156.13, A156.3)

Environmental: Indoor/Outdoor Approved

FrontHousing: -31°F (-35°C) to +151°F (66°C)

RearHousing: -31°F (-35°C) to +130°F (55°C)

Order #	Item #	Keyway	Description	Cat. Price
825-5800	E5831-B-WL-626-41	IC	Cylindrical Leverset	\$1792.00
825-5810	E5810-B-WL-626-41	IC	* Exit Trim	1932.00
825-5820	E5866-B-WL-626-41	IC	Mortise No Deadbolt	1960.00
825-5830	E5867-B-WL-626-41	IC	Mortise With Deadbolt	2002.00
825-5840	E5870-626-41	n/a	Stand Alone Controller	1512.00
825-5850	EP-FIPS-SW	n/a	FIPS Software for 5800 Locks	1400.00

* Exit Device Compatibility: Same as E5000 & E5700 on previous page.