

ASSA ABLOY

## SECURITRON™

Introduced in our  
Summer Sizzler



\* UL Listed

### Dual Sense Bar

The Dual Sense Bar is for use on magnetically locked, non-fire-rated doors. Specifically designed to address the most current building and life safety codes, the DSB features two independent switch circuits to release the lock. Simply touching the bar or engaging its mechanical movement will allow free egress. For indoor use only, the DSB can be installed on metal, aluminum or wood doors of all types. Meets "no special tools or knowledge" requirements.

#### Features and Benefits

- \* The most dependable exit device available for magnetically locked openings
- \* < 1/8" mechanical movement and ultra-reliable touch sense technology working together in a single exit bar
- \* Touch sensing and redundant movement-activated switches complies with current fire and life safety egress codes
- \* Uses same mounting pattern as the TSB-3
- \* Circuit board is immune to electrostatic discharge - switching power supplies, proximity and garment readers and neon signs
- \* Bounce resistant to false triggering from outside impact
- \* Three standard lengths: 36", 42" or 48"
- \* Like the TSB-3, the DSB allows field cutting to fit non-standard door widths
- \* DSB options include illuminated "Push To Exit" via internal fiber optic strip and MicroShield anti-microbial coating for superior germ resistance
- \* 16 ft. [4.8m] 22AWG 6 conductor cable and armored door cord included
- \* Available ElectroLynx ready
- \* Operates on either 12 or 24VDC
- \* Tested to 27,000 volts electrostatic discharge

Order #	Item #	Catalog Price
780-0500	DSB-CL	<b>\$549.00</b>
780-0510	DSB-BK	<b>561.20</b>

## SECURITRON™

Introduced in our  
Summer Sizzler



### Concealed Electrical Power Transfer



#### Features and Benefits

- \* Mortises into the edges of the door and frame
- \* Tamper resistant. No exposed openings prevents foreign objects from reaching the wires or jamming the device
- \* All metal construction including backboxes - no plastic
- \* 10 wire configuration includes 2-18 gauge wires
- \* Available with CAT-5E and ElectroLynx compatible connectors
- \* Installs above 2nd hinge
- \* 7/8" knockouts on back boxes accommodate EMF-type fittings
- \* Tested to 1,000,000 cycles
- \* Will not function with swing-clear hinges, pocket pivots, 3/4" offset pivots, 1-1/2" offset pivots, butt hinges over 6", center-hung doors or balanced doors

#### Specification Data

Hinge	Door Angle Range
</=5" Butt Hinge	0-180 Degrees
5-1/2" Butt Hinge	0-130 Degrees
6" Butt Hinge	0-110 Degrees

Order #	Item #	Catalog Price
780-0520	CEPT-10	<b>\$488.00</b>